



**CE** ZANZAR SISTEM s.p.a.  
C.so Europa Zona Ind.  
74023 Grottaglie (TA)  
Italy  
EN 13561 07  
zanzariera resistenza al vento  
classe tecnica: NPD

# Newkit40 Bars

lateral retractable screen

## Maintenance and utilization manual

ZANZAR SISTEM SPA which to thank you for buying NEWKIT 40; would you please read carefully this document and to store it. This manual is an integral part of the flyscreen and it provides all the informations for the installation, utilization and care.

The company reserves the right to change partially or totally the product without notice and accepts no liability for incorrect informations. Instructions, drawings and informations included in this manual are property of Zanzar Sistem Spa and cannot be reproduced totally or partially.



### WARNING

Flyscreens are intended to protect from insects, small rodents and reptiles and not to grant security: they do not prevent people or object to enter or a child to fall down from a window.

NEWKIT 40 is an horizontal retractable flyscreen, it's utilization is therefore recommended to adults. It is advisable to pay attention to childrens, as if the flyscreen is installed to a door the accidental push may cause an unwanted operation of the product; it also advisable to keep face and body fairly far to avoid collision due to a rapid movement of the handle profile due to the spring energy.

The product has a lower guide on the floor, it is therefore advisable to take care not to stumble over it. In the event of poor eyesight, the net could be difficult to be seen and it is advisable to put some coloured signs. Very rigid climate conditions can damage the flyscreen and in the event of strong wind it is advisable to disactivate it.

Do not remove the stick of the products with the CE mark.

The company accepts no liability if assembly instructions are not followed and reserve the right to change partially or totally the product without prior notice.



### UTILIZATION

#### ACTIVATION

To actionate the protection against insect, hold the handle and slide the handle bar along the guides to the closing profile till it close with the magnet.

#### DISACTIVATION

Warning to the energy accumulated by the spring which may cause the handle bar to slip from the hands. Hold firmly the handle bar and slide it along the guides and accompany it to the complete roll up of the screen inside the case.



### MAINTENANCE

Please carry out only the maintenance operations clearly indicated in the assembling instructions. The net do not favor the growth of micro-organism as consequence of waather conditions. Cleaning operations: wash the mesh and the profiles with water and soap, clear with clean water. Do not use solvents, oils, greasy and abrasive detergents.

It is advisable to use it at least once any three months to avoid the blocking of the mechanism. Any other maintenance activity has to be done by a centre recognized by Zanzar Sistem Spa. Corso Europa Z.I. - 74023 Grottaglie (TA) Italy.

The case consists of: cassette, innertube, net, handle and closing guide. Minimum size for the case is mm 550 as the spring size is mm 530. To manufacture shorter flyscreens it is necessary to cut the spring.

### Cutting guide


Case	Opening size - 16 mm
Handle bar	Opening size - 64 mm
Handle bar for central stop 2 shutters:	Opening size - 68 mm
Guides	Opening size - 55 mm
Closing profile	Opening size - 0 mm

### Spring load


Width	80	100	120	140
High	8	8	8	8

N.B. Spring load may vary of +- 2 turns


- 1** Measure the height (H) and the width (W) of the opening.




- 2** Cut the case as in the cutting guide.




- 3** Fix the right side cap; insert on the left side the spring and load it as explained in the table, by using an hexagonal key to put in the slot of the spring cap, and turning counterclockwise. Fix the cap on the case with the supplied screws (3.5x22).




- 4** Insert the sliders at the two extremities of the handle bar and fix the net in its slot.




- 5** Cut sliding profiles by the cutting instructions in the table.



- 6** Cut the closing profile at the same height of the door opening and insert the guide stoppers.




- 7** Install the case in the opening and fix it to the jamb by two screws each side.





- 8** Install the closing profile on the opposite jamb and fix it.

Warning: before assembling the screen check the magnets, if they do not adhere perfectly slip off the closing profile one and turn it upside down before putting it back in the profile. To facilitate this operation each magnet has a vertical strip: if correctly assembled the strips will be one opposite to the other.



- 9** Insert the lower guide in its slot on the case and on the closing profile and fix it with the guide stoppers. Repeat the operation with the upper guide.



**WARNING:** the flyscreen will work perfectly if it is not installed out of square; if necessary adjust the guides and use silicone. Rubber seal and PVC tape need to be bevelled by 3 mm.